



Type KST10KFS6-...

The swivelling crane control unit KST 10 is ergonomically designed and provides a high degree of comfort.

The standard design includes following:

Equipment boxes: plastic PU foam

The equipment boxes with the devices can be vertically and horizontally adjusted together with the armrests. Cabling is run through a duct in the cross-member. (Terminal block).

Seat: Comfortable spring mounted seat KFS 6, with an oilhydraulic vibration absorption system, weight adjustment and air-permeable artificial leather or textil material, with headrest.

Adjusting possibilities: Seat horizontally and vertically. Inclination of cushion, backrest and armrest also adjustable. Weight setting for optimum spring suspension.

Cross-member: Steel section, top of which can be raised to lay cabling. The seat can be tilted backwards so that the cable duct in the cross-member is accessible.

Swivel base: Zero-end-float spring-loaded bearing. Rotational movement 180° right, 90° left, stopped by friction brake.

Surface treatment: Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 9011 black. textured varnish

All non-painted metal parts are electrogalvanized and chromed.

Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C
Climate resistance	
Damp heat constant	IEC 60068-2-78
Damp heat cyclic	IEC 60068-2-30
Degree of protection	IP 54 IEC/EN 60529

Description data see catalog 5/028

Pos.				Weight kg	Type	Price EURO
1	Crane control unit standard design			48	KST 10	
2	Crane control unit standard design	not swivelled		48	KST 101	
3	Crane control unit standard design	without swivel base and cross-member		38	KST 102	
4						
5						
6	additional variations for driver's seat KFS 6 see catalog 2/134				KFS 6	
7						
8						
9						
10	Footrest mounted onto swivel base adjustable ± 30 mm			8		
11						
12						
13	Plate for horizontal manual adjustment of control unit adjustable ± 250 mm			95		
14						
15						
16						
17						
18						
19	Heating 2 x 2 kW with ventilator 230 V 50 Hz airvolume ca. 300 m³/h mounted on the swivel base sidewise					
20	Multi-axis controller V11, V 14, V 25, V 85 see catalog 1/110					
21						
22						
23						
24	Command and indicating devices see catalog 1/360					
30	Terminal block 4 mm² without wiring each terminal				KL	
31	Terminal block 4 mm² with wiring wire 1 mm² each terminal				KL	
32	External wiring single wire highly flexible 1,5 mm² 5 metre long					
33	Additional or subtract price each metre					
40	Special painted					
41	Indicating labels not engraved with 2 or 4 arrows					
42	Engraving, each 10 characters					

